# VinaGARD Translucent

## Flexible, Double Coated Protective Fabric from... Vintex Inc

**Frosty AW53-14**

**V-Clear 267**

## Product Features and Benefits

- allows light transmission
- superior low temperature performance
- flame retardant for the life of the fabric
- U.V. resistant for long life
- dielectrically & thermally weldable
- rot, mildew & fungus resistant
- dimensionally stable; shrink resistant
- tear and abrasion resistant

## Typical Physical Properties

| Property | Frosty AW53-14 | V-Clear 267 | Test Method |
|---|---|---|---|
| Total Weight (oz/yd²): | 14 | 13 | D3776 |
| Tear (lbs): | 84 (w) x 65 (f) | 43 (w) x 44 (f) | D1117 |
| Tensile (lb/inch): | 245 (w) x 232 (f) | 109 (w) x 111 (f) | D751 |
| Adhesion (lb/inch): | 18 (w) x 22 (f) | Excellent | D751 |
| Cold Crack (1/8 Mandrel): | -45°C | -35°C | D2136 |
| Weatherometer: | $\triangle E < 2$ @ 5,000 hrs | 2000 hours – very slight color change | ASTM G155 CAM 7 |
| Flame Resistance: | NFPA701 2004 CAN/ULC S109 L&S | FMVSS302 NFPA701 –1989-large ULC S109 L&S | |
| Stock Width: | 61 " | 61 " | |
| Stock Roll: | 50 Meters - 84 lbs | 50 Meters - 76 lbs | |

## Some Recommended Uses

- enclosures
- curtains

**See reverse for information on our company and other product capabilities**

This information is obtained by industry accepted test methods and represents typical data. It is for your general information only. There are no warranties expressed or implied. The information is furnished upon the condition that the people receiving it shall conduct their own tests to determine the suitability of our material for the particular application involved.

Vintex Inc

ISO 9001:2000 Registered

Customer Service Phone: 1-800-846-8399
Customer Service Fax: 1-888-256-0004

Rev: Jan 19/06- June 25/03
TPP# 0008/0007